

63mm Diameter Combined Pressure & Temperature Gauge

Application

Typically used in heating applications and systems where limited space prevents the use of separate pressure and temperature gauges.

Specifically designed for the UK's heating / ventilation, mechanical services and air conditioning markets.



Description

Nominal Size

63mm

Accuracy

+/- 2.5% FSD - Pressure

BS EN13190 - Class 2 - Temperature

Scales

BAR Upper Black & Blue - Pressure

°C Lower Black & Red - Temperature

Ranges

0/4 BAR Pressure & 0/120°C Temperature

0/6 BAR Pressure & 0/120°C Temperature

Mounting Options

Centre Back - Direct Mounting Only (standard)

Ingress Protection

IP 40 as per EN 60529

Case

ABS Plastic - Black

Window

Acrylic - Crystal clear, push fit

Pressure Element

CU Alloy - Sealed Bourdon tube C-Type

Temperature Movement

Precision Bimetal Spiral

Pointer

Plastic - Black

Dial

Aluminium - White

Process Connection

Brass - 1/2" BSPT (tapered) male - Non Return Valve

Special Options

Other scales/ranges

Customer logo dials

**FULL RANGE OF MATCHING HVAC SPECIFICATION PRESSURE GAUGES AND
ACCESSORIES ALSO AVAILABLE**



Unit 4C | Woodhall Business Park | Sudbury | Suffolk | CO10 1WH | United Kingdom
T: +44 (0) 1787 882038 | F: +44 (0) 1787 882039 | E: info@modusgauges.com | W: modusgauges.com